

How to:



Rotary Floor Machine Cleaning Of Carpet

Why Rotary Carpet Cleaning?

Rotary shampooing is a restorative method of carpet cleaning. It removes deeply imbedded soils, which surface cleaning cannot reach. Care should be taken not to over wet the carpet. This method is a two person job with the second person using a wet vac immediately after the first person shampoos with a rotary machine.

Equipment / Materials Needed:

- Rotary floor machine with solution tank and shower fed shampoo brush. (Nylon or Polypropylene.)
- Wet Vacuum
- Carpet Shampoo (Husky 1120)
- Pile Brush of carpet rake.
- Fans

Procedure: Rotary Shampooing of Carpet.

1. Vacuum carpet thoroughly and pre-spot.
2. Position wet floor signs.
3. Mix carpet solution according to manufactures directions.
4. Attach shampoo brush to scrubber and lubricate brush before shampooing.
5. Pour shampoo solution into solution tank and scrub carpet area until a layer of foam is generated.
6. Work across the carpet in a slow, side to side motion. Move slowly backward, making sure to overlap the cleaned area. Be careful not to over wet the carpet.
7. Wet vacuum immediately to remove soil laden foam and speed drying. Use defoamer in tank if too much foam is generated.
8. For high pile carpet, use a carpet rake or a pile brush to brush the carpet against the pile.
9. Use fans to speed up drying.
10. When dry, vacuum area.
11. Clean up equipment and return to storage.
12. Do not stand scrubber on shampoo brush or you will flatten the bristles.

Fact:

Spots should be removed as soon as they are discovered. Spots left to long can discolor and stain the carpet depending on the makeup of the stain and type of carpet.

Stevens Chemical Company, 5846 N. Clark Street, Chicago IL 60660

Tel: 773-784-8450 • Fax: 773-784-8496 • stevenschemical@earthlink.net • www.stevenschemical.com